

# ABRASIFLEX HD



Inner Tube: black synthetic rubber tube that is abrasion resistant.

Reinforcement: high tensile textile braid, with steel helix wire. Wire option for purely discharge services

80°C  
MÁX.

Cover: smooth (wrapped) made from black rubber that is abrasion, weather and ozone resistant.

## APPLICATION

Recommended for the aggressive suction and transfer of abrasive materials in general (sand, ore, cement, fertilizers, etc.) in a dry or aqueous medium. Robust product that is easy to handle. Full-face end fittings available only up to pressure of 150PSI, above that, only integral nipples are available.



## END FITTINGS



R



BA



P



FF



NPL



NFG



NFF



NRM



75PSI

2"

2 7/8"

20

3.13

620

306

3"

3 7/8"

20

4.86

620

456

4"

5 1/8"

20

6.62

620

612

6"

7 1/4"

20

12.24

620

912

8"

9 3/8"

20

18.72

620

1218

10"

11 3/4"

20

28.29

620

1524

12"

13 7/8"

20

36.41

620

1830

16"

18 1/8"

10

52.50

620

2436

2"

2 7/8"

20

3.70

620

306

3"

4 1/8"

20

5.64

620

456

4"

5 1/4"

20

8.39

620

612

6"

7 1/2"

20

14.00

620

912

8"

9 7/8"

20

24.50

620

1218

10"

11 7/8"

20

32.52

620

1524

12"

14 1/4"

20

43.29

620

1830

16"

18 5/8"

10

65.37

620

2436

150PSI

2"

3 1/8"

20

4.04

620

306

2 1/2"

3 3/4"

20

5.65

620

390

3"

4 1/4"

20

6.59

620

456

4"

5 1/2"

20

10.10

620

612

5"

6 5/8"

20

13.66

620

762

6"

7 3/4"

20

17.21

620

912

8"

10 1/8"

20

27.05

620

1218

10"

12 3/8"

20

38.21

620

1524

300PSI

