

# ABRASIFLEX




## APPLICATION

Recommended for lower-duty suction and transfer of abrasive materials in general (sand, ore, cement, fertilizers, etc.) in a dry or aqueous medium. A lightweight and extremely flexible product that is easy to handle. Full-face end fittings available only up to pressure of 150PSI, above that, only integral nipples are available.



## END FITTINGS



## 75PSI

2"	2 3/4"	20	2,35	620	306	
3"	3 7/8"	20	4,34	620	456	
4"	4 7/8"	20	5,58	620	612	
6"	6 7/8"	20	9,99	620	912	
8"	8 7/8"	20	13,85	620	1218	

## 150PSI

2"	2 3/4"	20	2,62	620	306
3"	3 7/8"	20	4,34	620	456
4"	4 7/8"	20	5,58	620	612
6"	7 1/8"	20	10,68	620	912
8"	9 1/4"	20	16,20	620	1218
10"	11 3/8"	20	23,04	620	1524
12"	13 1/2"	20	30,36	620	1830
14"	15 1/2"	10	34,78	620	2130

## 300PSI

2"	2 3/4"	20	2,62	620	306
3"	3 7/8"	20	4,90	620	456
4"	4 7/8"	20	6,28	620	612
6"	7 1/4"	20	12,14	620	912
8"	9 3/8"	20	18,00	620	1218
10"	11 5/8"	20	25,85	620	1524
12"	13 5/8"	20	31,74	620	1830
14"	15 5/8"	10	35,63	620	2130

