

AGUABRUTA



80°C
MAX.

Inner Tube: black synthetic rubber tube.

Reinforcement: high tensile textile braid with steel helix wire.


Cover: smooth (wrapped) and made from black rubber that is abrasion, weather and ozone efficient with a yellow continuous transfer label.

APPLICATION

For medium and low-duty services involving water pumping and suction in industry, agriculture or civil construction applications. Full-face end fittings available only up to pressure of 150PSI, above that, only integral nipples are available.



END FITTINGS



1"



1 1/2"



20



0,77



620



100

75 PSI

2"	2 5/8"	20	1,70	620	204
4"	4 5/8"	20	4,37	620	404
6"	6 3/4"	20	7,56	620	760
8"	8 7/8"	20	11,90	620	1015
10"	10 7/8"	20	15,52	620	1270
12"	12 7/8"	20	18,46	620	1830
14"	15 1/4"	10	29,31	620	2130

150 PSI

2"	2 5/8"	20	1,93	620	204
4"	4 3/4"	20	4,68	620	404
6"	6 7/8"	20	9,78	620	760
8"	8 7/8"	20	12,81	620	1015
10"	11 1/8"	20	18,88	620	1270
12"	13 1/8"	20	22,43	620	1830
14"	15 3/8"	10	30,02	620	2130

300 PSI

2"	2 5/8"	20	1,93	620	204
4"	4 3/4"	20	4,68	620	404
6"	7 1/8"	20	9,78	620	760
8"	8 7/8"	20	12,81	620	1015
10"	11 1/4"	20	18,88	620	1270
12"	13 1/4"	20	22,43	620	1830
14"	15 1/2"	10	30,02	620	2130

