

ALIFLEX SD SUCTION AND DISCHARGE



Inner tube: Non-toxic white tube, soft, resistant to oil and free of phthalates.

Reinforcement: high tensile textile braid with steel helix wire.

Cover: Smooth (wrapped), made from blue abrasion, weather and ozone resistant rubber.

**140°C
MÁX.**


APPLICATION

Suction and discharge of alimentary products such as wine, beer, milk, olive oil, fats, wax, fruit juice, etc. Developed for unloading docks in the food processing and transfer industries between liquid and pasty foodstuffs tanks.

Flexible and easy to use product with excellent resistance to torsion and with great resistance to temperature changes. It can be sterilized with steam at 130 ° C for 30 minutes or with a 5% soda solution. soda at 5%.



END FITTINGS



R TPRM TPF TPG TPEM TPAL



1/2" 7/8" 10 0.59 620 156

1" 1 1/2" 10 1,15 620 300

2" 2 5/8" 10 2,58 620 612

3" 3 5/8" 10 4,53 620 912

4" 4 5/8" 10 5,58 620 1212

5" 5 7/8" 10 9,51 620 1524

6" 6 7/8" 10 12,07 620 1824

150PSI

1/2" 7/8" 10 0,56 620 156

1" 1 1/2" 10 1,08 620 300

2" 2 5/8" 10 2,58 620 612

3" 3 5/8" 10 4,19 620 912

4" 4 5/8" 10 5,17 620 1212

5" 5 7/8" 10 8,96 620 1524

6" 6 7/8" 10 11,43 620 1824

300PSI

