BOCA DE FORNO HD



Inner Tube: black nonconductive synthetic rubber tube (electric resistance greater than 1000 MOhms)..

Reinforcement: high tensile textile braid.

-Cover: smooth made from vulcanized fiberglass and orange flame-retardant synthetic rubber that is resistant to a maximum external temperature of up to 550°C.

APPLICATION

Hose used at the furnace doors to cool the electrical cables in foundries, the glass industry and for services requiring full electrical insulation of the hose together with resistance to heat caused by irradiation, direct flame and splashes of incandescent materials.





END FITTINGS



R

U	7
	Ĺ
L)
	4

3/4 "	1 5/8"	20	1,39	N/A	114
1"	17/8"	20	1,94	N/A	150
1 1/4"	2 1/4"	20	2,41	N/A	186
1 1/2"	2 1/2"	20	2,74	N/A	228
2"	3 1/8"	20	3,82	N/A	306
2 1/2"	3 5/8"	20	4,59	N/A	390
3"	4 1/8"	20	5,35	N/A	456
4"	5 3/8"	20	8,31	N/A	612

300PSI

3/4 "	1 3/4"	20	1,71	N/A	114
1"	2 1/8"	20	2,28	N/A	150
1 1/4"	2 3/8"	20	2,66	N/A	186
1 1/2"	2 5/8"	20	3,17	N/A	228
2"	3 1/8"	20	3,90	N/A	306
2 1/2"	3 5/8"	20	4,67	N/A	390
3"	4 1/4"	20	5,96	N/A	456
4"	5 1/2"	20	9,08	N/A	612

