DISCHARGE OF CHEMICAL PRODUCTS



Inner Tube: butyl rubber inner tube.

Reinforcement: high tensile textile braid.

Cover: smooth (wrapped), made from black rubber that is abrasion, weather and ozone resistant with a violet continuous transfer label.

APPLICATION

Robust hose indicated for heavy services of transfer of a large amount of chemical products (acids, bases, oxidizing solutions and contaminated industrial waters) used in the industry. Full-face end fittings available up to 150PSI pressure only, above only stainless steel integral nipples.



END FITTINGS





BA







NFF



FF

NFG

NRM

1 [/0"

1	ľ	Ī	T	١
4	<u> </u>			,







_	_		_	_	
1"	15/8"	20	1,01	N/A	300
1 1/4"	17/8"	20	1,21	N/A	384
1 1/2"	2 1/8"	20	1,40	N/A	456
2"	2 5/8"	20	1,86	N/A	612
3"	3 7/8"	20	3,52	N/A	912
4"	4 7/8"	20	4,54	N/A	1212
6"	6 7/8"	20	8,17	N/A	1824
8"	8 7/8"	20	10,69	N/A	2436

1"	15/8"	20	1,01	N/A	300
1 1/4"	17/8"	20	1,21	N/A	384
1 1/2"	2 1/8"	20	1,40	N/A	456
2"	2 5/8"	20	1,86	N/A	612
3"	3.7/8"	20	3,52	N/A	912
4"	4 7/8"	20	4,54	N/A	1212
6"	6 7/8"	20	8,17	N/A	1824
8"	8 7/8"	20	10,69	N/A	2436

1"	1 5/8"	20	1,07	N/A	300
1 1/4"	17/8"	20	1,29	N/A	384
1 1/2"	2 1/4"	20	1,48	N/A	456
2"	2 3/4"	20	1,98	N/A	612
3"	3 7/8"	20	3,61	N/A	912
4"	4 7/8"	20	4,92	N/A	1212
6"	7 1/8"	20	8,69	N/A	1824
8"	8 7/8"	20	11,37	N/A	2436

