

FLATFLEX OIL



**80°C
MAX.**

Inner Tube: black synthetic rubber tube resistant to oil derivatives, biodiesel and alcohol.

Reinforcement: high tensile textile braid with static conductive filament.


Cover: smooth (wrapped), made from black rubber that is abrasion, weather and oil resistant with a blue continuous transfer label.

APPLICATION

Flat rubber hose recommended for oil derivative transfer and discharge services, covering a variety of fuels, such as: gasoline, alcohol, biodiesel and diesel oil, among others. Excellent for applications requiring a lightweight and flexible hose. Full-face end fittings not available for this product..



END FITTINGS



75PSI

1"	1 1/2"	20	0,58	N/A	N/A	
1 1/2"	1 7/8"	20	0,81	N/A	N/A	
2"	2 3/8"	20	1,05	N/A	N/A	
2 1/2"	2 7/8"	20	1,30	N/A	N/A	
3"	3 1/2"	20	1,54	N/A	N/A	
3 1/2"	3 7/8"	20	1,78	N/A	N/A	
4"	4 3/8"	20	2,03	N/A	N/A	

150PSI

1"	1 1/2"	20	0,58	N/A	N/A
1 1/2"	1 7/8"	20	0,81	N/A	N/A
2"	2 3/8"	20	1,05	N/A	N/A
2 1/2"	2 7/8"	20	1,30	N/A	N/A
3"	3 1/2"	20	1,54	N/A	N/A
3 1/2"	3 7/8"	20	1,78	N/A	N/A
4"	4 3/8"	20	2,03	N/A	N/A

300PSI

1"	1 1/2"	20	0,65	N/A	N/A
1 1/2"	1 7/8"	20	0,89	N/A	N/A
2"	2 1/2"	20	1,16	N/A	N/A
2 1/2"	2 7/8"	20	1,40	N/A	N/A
3"	3 1/2"	20	1,67	N/A	N/A
3 1/2"	3 7/8"	20	1,92	N/A	N/A
4"	4 1/2"	20	2,20	N/A	N/A

