## FLATFLEX WATER



Inner Tube: black synthetic rubber tube.

Reinforcement: high tensile textile braid..

Cover: smooth (wrapped) and made from black rubber that is abrasion, weather and ozone efficient with a yellow continuous transfer label.

## **APPLICATION**

Flat general use hose for discharging water. Excellent for applications requiring a lightweight and flexible hose.

Full-face end fittings available only up to pressure of 150PSI, above that, only integral nipples are available.



**END FITTINGS** 



R



FF







NFF



NRM

5 PSI

		TITITI	44	FIT	
1"	1 1/2"	20	0,54	N/A	N/A
2"	2 3/8"	20	0,97	N/A	N/A
2 1/2"	2 7/8"	20	1,21	N/A	N/A
3"	3 1/2"	20	1,44	N/A	N/A
4"	4 3/8"	20	1,78	N/A	N/A
6"	6 1/2"	20	3,03	N/A	N/A
8"	8 1/2"	20	4,01	N/A	N/A
10"	10 1/2"	20	4,98	N/A	N/A

**120 PSI** 

1"	1 1/2"	20	0,54	N/A	N/A
2"	2 3/8"	20	0,97	N/A	N/A
2 1/2"	2 7/8"	20	1,21	N/A	N/A
3"	3 1/2"	20	1,44	N/A	N/A
4"	4 3/8"	20	1,88	N/A	N/A
6"	6 1/2"	20	3,30	N/A	N/A
8"	8 3/8"	20	4,34	N/A	N/A
10"	10 5/8"	20	6,84	N/A	N/A

300 PSI

1"	1 1/2"	20	0,61	N/A	N/A
2"	2 1/2"	20	1,09	N/A	N/A
2 1/2"	2 7/8"	20	1,32	N/A	N/A
3"	3 1/2"	20	1,56	N/A	N/A
4"	4 1/2"	20	2,08	N/A	N/A
6"	6 5/8"	20	4,16	N/A	N/A
8"	8 5/8"	20	6,31	N/A	N/A
10"	10 3/4"	20	7,82	N/A	N/A

