

MINERALFLEX HD



Inner Tube: black synthetic rubber tube that is resistant to high abrasion.

Reinforcement: high tensile textile braid with steel helix wire.

80°C
MÁX.


Cover: smooth (wrapped), made from black rubber that is highly abrasion, weather and ozone resistant.







APPLICATION

Large bore hose especially developed for the suction and aggressive settling of iron ore slurry and other highly abrasive materials in a dry or aqueous medium.



END FITTINGS



| |  |  |  |  |  |  |
|-----|---|---|---|---|---|---|
| 4" | 5 1/8" | 20 | 6,82 | 620 | 612 | |
| 6" | 7 3/8" | 20 | 12,45 | 620 | 912 | |
| 8" | 9 5/8" | 20 | 21,09 | 620 | 1218 | |
| 10" | 11 3/4" | 20 | 28,44 | 620 | 1524 | |
| 12" | 13 7/8" | 20 | 37,87 | 620 | 1830 | |
| 14" | 15 7/8" | 10 | 43,64 | 620 | 2130 | |
| 16" | 18 1/8" | 10 | 52,66 | 620 | 2436 | |

75PSI

150PSI

| | | | | | |
|-----|---------|----|-------|-----|------|
| 4" | 5 1/4" | 20 | 8,20 | 620 | 612 |
| 6" | 7 1/2" | 20 | 16,29 | 620 | 912 |
| 8" | 9 3/4" | 20 | 24,04 | 620 | 1218 |
| 10" | 11 7/8" | 20 | 29,91 | 620 | 1524 |
| 12" | 14 1/8" | 20 | 40,51 | 620 | 1830 |
| 14" | 16 1/8" | 10 | 48,15 | 620 | 2130 |
| 16" | 18 1/4" | 10 | 57,71 | 620 | 2436 |
| 20" | 22 3/4" | 10 | 90,30 | 620 | 3048 |

