

OIL



**80°C
MÁX.**

Inner Tube: black synthetic rubber tube resistant to oil derivatives, biodiesel and alcohol.

Reinforcement: high tensile textile braid with static conductive filament.


Cover: smooth (wrapped), made from black rubber that is oil, abrasion, ozone and weather resistant with a blue continuous transfer label.

APPLICATION

Recommended for oil derivative transfer and discharge services, covering a wide variety of fuels, such as: gasoline, alcohol, biodiesel and diesel oil, among others. Lightweight product that is easy to handle. Full-face end fittings not available for this product.



END FITTINGS



1"	1 1/2"	20	0,83	N/A	300					
1 1/4"	1 3/4"	20	0,96	N/A	384					
1 1/2"	1 7/8"	20	1,11	N/A	456					
2"	2 1/2"	20	1,44	N/A	612					
2 1/2"	2 7/8"	20	1,76	N/A	756					
3"	3 1/2"	20	2,07	N/A	912					
4"	4 1/2"	20	2,70	N/A	1212					
6"	6 3/4"	20	5,45	N/A	1824					

75PSI

1"	1 5/8"	20	0,90	N/A	300
1 1/4"	1 7/8"	20	1,05	N/A	384
1 1/2"	2 1/8"	20	1,20	N/A	456
2"	2 5/8"	20	1,56	N/A	612
2 1/2"	3 1/8"	20	2,02	N/A	756
3"	3 5/8"	20	2,37	N/A	912
4"	4 5/8"	20	3,12	N/A	1212
6"	6 7/8"	20	6,70	N/A	1824

150PSI

1"	1 5/8"	20	0,92	N/A	300
1 1/4"	1 7/8"	20	1,09	N/A	384
1 1/2"	2 1/8"	20	1,24	N/A	456
2"	2 5/8"	20	1,60	N/A	612
2 1/2"	3 1/8"	20	1,90	N/A	756
3"	3 3/4"	20	3,01	N/A	912
4"	4 3/4"	20	4,11	N/A	1212
6"	6 7/8"	20	6,70	N/A	1824

300PSI

