

SUCTION AND DISCHARGE OF OIL



Inner Tube: black synthetic rubber tube resistant to oil derivatives, biodiesel and alcohol.

Reinforcement: high tensile textile braid with a steel helix wire and static conductive filament.

80°C
MÁX.

Cover: smooth (wrapped), made from black rubber that is oil, abrasion, ozone and weather resistant with a blue continuous transfer label.

APPLICATION

Recommended for oil derivative suction and discharge services, covering a wide range of variety of fuels, such as: gasoline, alcohol, biodiesel and diesel oil, among others. Lightweight and extremely flexible product. Full-face end fittings not available for this product.



END FITTINGS



R



P



BA



NPL



NFG



NFF



NRM



TPRM



TPF



TPG



TP

75PSI

1"	1 1/2"	20	0,95	620	100	
2"	2 5/8"	20	1,93	620	204	
3"	3 5/8"	20	3,68	620	304	
4"	4 3/4"	20	4,80	620	404	
6"	6 7/8"	20	9,51	620	760	
8"	8 7/8"	20	13,74	620	1015	

150PSI

1"	1 5/8"	20	1,10	620	100
2"	2 5/8"	20	2,05	620	204
3"	3 5/8"	20	3,74	620	304
4"	4 3/4"	20	4,88	620	404
6"	6 7/8"	20	10,20	620	760
8"	8 7/8"	20	14,09	620	1015

300PSI

1"	1 5/8"	20	1,14	620	100
2"	2 5/8"	20	2,05	620	204
3"	3 3/4"	20	3,87	620	304
4"	4 3/4"	20	5,00	620	404
6"	6 7/8"	20	11,01	620	760
8"	9 1/8"	20	15,14	620	1015

