WATER AIR



Inner Tube: tube made from /black synthetic rubber.

Reinforcement: high tensile textile braid.

Cover: smooth (wrapped) and made from black rubber that is abrasion, weather and ozone efficient with a yellow continuous transfer label.

APPLICATION

General use hose for applications with lower requirements for transporting water and air in industry. It is lightweight, flexible and easy to handle.



END FITTINGS













R

BA

TPRM

TPFF

TPFG TPEM

PS .	
	S
	<u>a</u>
\mathbf{L}	\mathbf{L}

		TITITI	474	AT .	
1/2"	1 1/8"	20	0,56	N/A	156
1"	15/8"	20	0,92	N/A	300
2"	2 5/8"	20	1,64	N/A	612
3"	3 5/8"	20	2,34	N/A	912
4"	4 5/8"	20	3,48	N/A	1212
5"	5 5/8"	20	4,28	N/A	1524
6"	6 5/8"	20	5,08	N/A	1824
8"	8 7/8"	20	8,98	N/A	2436

S
<u>a</u>
Ŋ

1/2"	1 1/8"	20	0,57	N/A	156
1"	15/8"	20	0,92	N/A	300
2"	2 3/4"	20	1,88	N/A	612
3"	3 3/4"	20	2,98	N/A	912
4"	4 3/4"	20	3,87	N/A	1212
5"	5 7/8"	20	5,50	N/A	1524
6"	6 7/8"	20	7,49	N/A	1824
8"	9 1/4"	20	12,79	N/A	2436

300 PSI

1/2"	1 1/8"	20	0,63	N/A	156
1"	15/8"	20	1,07	N/A	300
2"	2 7/8"	20	2,55	N/A	612
3"	3 7/8"	20	3,78	N/A	912
4"	4 7/8"	20	5,45	N/A	1212
5"	6 1/4"	20	7,84	N/A	1524
6"	7 3/8"	20	10,54	N/A	1824
8"	9 3/8"	20	14,86	N/A	2436

